



108 gr

TITAN GARA WORLD CUP

Ski brake	NO SKI BRAKE
Weight	108 gr
Downhill angle	0.7°
Uphill angle	0° - 6°
Heel setting	No setting
Material	Ergal - Titanium - Steel -Technopolymer Titanium
Release	TITAN SPRING

RACE YELLOW SKINS



GARA WORLD CUP QC

Cod.42060 ORTLES CORK HANDLE
Cod.42061 ORTLES CLIP STRAP
GRIP SUPPORT

Material: Ergal Ø 16x0.8
Strap: Ortles Clip strap
Handle: Ortles Cork handle
Basket: Gara QC basket+Widia
Size: 110cm-145 cm each
5 cm
Weight: 185 gr 140cm

Cod.42062 TIPS+BASKET ORTLES QC
Cod.42042 BASE AND NUT QC
Cod.42043 BASKET GARA QC
Cod.42044 BASKET TORNADO BIG QC
Cod.42045 ROLLSKI TIP QC



ERGAL Ø 16x0.8

Cod.42043 BASKET GARA
Quick Change



GRAZIE PER AVER SCELTO SKI TRAB

Gli sci contraddistinti dal marchio "made in Bormio" sono garantiti per 3 anni contro i difetti di fabbricazione. La garanzia parte dalla data di acquisto dello sci (fa fede la ricevuta di acquisto). Se riscontrato un difetto di fabbricazione lo sci potrà essere sostituito o riparato a discrezione di SKI TRAB. In ogni caso se ne garantirà il perfetto funzionamento. La garanzia non copre i danni allo sci causati da forti impatti dovuti ad uso non appropriato o da cadute, danni allo sci causati da contatti contro sassi, rocce o altre superfici diverse dalla neve, abrasioni, intaccature e sfilamenti della superficie o dei fianchi e delle estremità. Non copre inoltre danni causati da infiltrazioni d'acqua dovute ad abrasioni sul fianco o da fori attacchi non sigillati, scolorimenti della grafica, danni causati da montaggi impropri o montaggi di attacchi che non utilizzano viti appropriate o attacchi che lacerano la superficie dello sci perché non rispettosi degli standard.

THANK YOU FOR CHOOSING SKI TRAB.

All skis marked with the brand "made in Bormio" are guaranteed against manufacturing faults for 3 years. 3-year warranty from the date of purchase on the sale receipt. If a manufacturing fault is found, the skis can be replaced or repaired at SKI TRAB's discretion. In any case, perfect functioning will be ensured. The warranty does not cover damage to the skis caused by strong impacts due to improper use or falls, damage to the skis resulting from contacts with stones, rocks or any surfaces other than snow, abrasions, cracks/cuts and fraying of the surface or the sidewalls as well as of the tips and tails of the skis. This warranty doesn't also cover damage caused by water infiltration due to abrasions on the sidewall or unsealed ski-binding holes, fading of the graphics, damage resulting from improper mounting or mounting of ski-binding with inappropriate screws or ski-bindings tearing the surface of the skis because not in compliance with Standards.



SKITRAB.COM

SKI TRAB



GARA WORLD CUP 60




SIZE (CM)	155
WEIGHT (GR)	685
RADIUS (MT)	21.3
SURFACE (CM2)	11.13
TORSION	CARBON
SIDECUT (MM)	92/64/79

GARA WORLD CUP 60 cod. 13175w

4 LAYER

GARA CONTROL

Reliability is guaranteed by the 14-Layer Gara Control construction wrapped in carbon to maximise the anti-torsion force and by the special bridge between the edges to better withstand impacts with rocks. Superlightweight honeycomb core in aramid and wood, new radiuses and new flex 60 that improves skiing and reduces energy consumption in ascent - fundamental when every little counts.



- 1 CONSTRUCTION: CAP QUADRIAXIAL
- 2 PROTECTION SHEET: PA LIGHT PROTECTION
- 3 CORE: ARAMID-ASH WOOD-LIGHT WOOD
- 4 CARBON SUPPORT: BIAXIAL CARBON
- 5 EDGE: STEEL 52HRC
- 6 TORSION REINFORCEMENTS: CARBON HM
- 7 CAP REINFORCEMENT: CARBON-BASALT
- 8 BASE: SINTERED BLACK BASE
- 9 FINISHING: EDGE RADIAL - TUNING 89°
- 10 BASE FINISHING: RACE MICROSTRUCTURED
- 11 BINDING PLATE/ANTI-TORSIONAL PLATE: MULTI LAYER FIBERGLASS

ARAMID
HONEYCOMB AERO CORE

ARAMID / NOMEX

PLACE OF ORIGIN: EUROPE

USE: AEROSPACE AND AERONAUTIC

DENSITY: 70 KG M³

COMPRESSIVE STRENGTH MPA 10

CHARACTERISTICS: LIGHTWEIGHT, FLEXIBLE



LIGHT WOOD

PLACE OF ORIGIN: THE EAST

USE: WOODWORK, SKIS

DENSITY: 270/300 KG M³

COMPRESSIVE STRENGTH MPA 18

CHARACTERISTICS: LIGHTWEIGHT, EASY TO PROCESS



FRAXINUS L. / ASH TREE

PLACE OF ORIGIN: EUROPE

USE: BUILDING INDUSTRY, TOOLS, FUEL

DENSITY: 600/700 KG M³

COMPRESSIVE STRENGTH MPA 30

CHARACTERISTICS: SOLID AND HIGHLY FLEXIBLE

≡ ULTRALIGHT CORE COMPONENTS

CONTROL FLEX

DUOTAIL

HIBOX

HICONNECT

NOSHOCK